

# Requirements Document

# PRC-RD-SH-8471 Ergonomics

Revision 0, Change 1

Published: May 17, 2009 Effective: May 17, 2009

Project: CH2M HILL Plateau Remediation Company Topic: Occupational Safety & Industrial Hygiene

**Technical Authority: E.L. Stairet Functional Manager: T.L. Vaughn** 

# **Administrative Use**



Rev. 0, Chg. 1

## **PRC-RD-SH-8471**

Page 2 of 7

## **Ergonomics**

Published Date: 5/17/09 Effective Date: 5/17/09Error!
Reference source not found.

#### **CHANGE SUMMARY**

AJHA: N/A
Periodic Review Due Date: 4/6/2014

HRB Date: N/A
Validation Date: N/A

Rev. 0, Chg. 1 PR#: PRC-09-0389 USQ Screen Number:

Editorial: GCX-2 TP: Exempt

#### **Description of Change**

Editorial changes to align with current CHPRC procedures format, and reference and form numbers and titles.

## Page 3 of 7

# **Ergonomics**

Published Date: 5/17/09

Effective Date: 5/17/09Error! Reference source not found.

#### **TABLE OF CONTENTS**

1.0	PURPOSE AND SCOPE	4
	REQUIREMENTS	
-	SOURCES	
	3.1 Requirements	6
	3.2 References	
4.0	APPENDIXES	6

## **Ergonomics**

Published Date: 5/17/09 Effective Date: 5/17/09Error!
Reference source not found.

#### 1.0 PURPOSE AND SCOPE

This Level 1 requirements document is applicable to CH2M HILL Plateau Remediation Company (CHPRC) Team employees and establishes requirements to ensure that conditions presenting potential ergonomic-related hazards to employees are identified and controlled. The general requirements approach used in this document recognizes the varied work activities associated with each of the CHPRC Projects/Functions. This variety necessitates flexibility in addressing ergonomic-related conditions.

CHPRC Projects/Functions performing CHPRC work scope shall make ergonomics a consideration in their overall safety program. In line with Voluntary Protection Program (VPP) and Integrated Safety Management Systems (ISMS) principles, efforts will focus on: Management commitment and leadership, Employee involvement, Hazard identification and analysis, Hazard elimination, reduction or control, Training, and Continuous improvement achieved by sharing of lessons learned.

#### 2.0 REQUIREMENTS

**NOTE:** For the tables in this section under the requirement "type" column, "V" means verbatim and "I" means interpreted.

#	REQUIREMENT	TYPE V or I	SOURCE
1.	Work areas and tasks shall be evaluated to identify those with potential ergonomic-related hazards including repetition, awkward posture, force, vibration, and contact stress.  Physical strength and conditioning of the involved personnel will also be considered.	1	10CFR851.21 (a) (1)-(8)
2.	The Job Hazard Analysis (JHA) process (PRC-PRO-WKM-079) shall be used to identify, evaluate, control, and communicate potential hazards relative to discrete work activities/tasks to be performed, and establish an appropriate level of controls.	1	10CFR851.21 (a) (1)-(8)
3.	Measures shall be implemented that prevent or control to the extent possible ergonomic-related hazards specific to the involved work area and activities. Hazard controls must be selected based on the following hierarchy:  a. Elimination or substitution of the hazards where	I	10CFR851.22 (a)
	feasible and appropriate; b. Engineering controls where feasible and appropriate;		
	c. Work practices and administrative controls that limit worker exposures; and		
	d. Personal protective equipment.		
	<b>NOTE:</b> Refer to <u>Appendix A</u> for examples.		
4.	Mechanical lifting devices shall be used for lifting or moving heavy objects when possible.	1	10CFR851.22 (a) (2) (i)

# **Ergonomics**

Published Date: 5/17/09

Effective Date: 5/17/09Error! Reference source not found.

#	REQUIREMENT		TYPE V or I	SOURCE
5.	Employees shall not attempt to singularly lift objects that exceed physical capabilities or are greater than 55 pounds (24.95 kgs) without a hazards analysis.		I	10CFR851.22 (a) (2) (i)
6.	The handling of material-containing drums shall be conducted as follows:			10CFR851.22 (a) (2) (i)
		echanical and/or powered assist devices will be used hen possible.		
		ngle person unassisted manual lift(s) of a drum are nited to 55 pounds (24.95 kgs) or less.		
		wo-person manual lifts of a drum are limited to 55 bunds (24.95 kgs) or less per person.		
	dr	ngle person unassisted manual push (tipping) of a rum in an upright position is limited to 240 pounds 08.86 kgs) or less.		
	up	wo-person manual push (tipping) of a drum in an oright position is limited to 240 pounds (108.86 kgs) er person.		
	dr	ngle person unassisted manual pull (tipping) of a rum in an upright position is limited to 220 pounds 9.79 kgs) or less.		
	up	wo-person manual pull (tipping) of a drum in an oright position is limited to 220 pounds (99.79 kgs) per erson.		
	to ho	ngle person manual raising from a horizontal position a vertical position or lowering from an upright to prizontal position of a drum is not permitted due to the wkward body positioning needed to complete the task.		
	to ho	wo-Person manual raising from a horizontal position a vertical position or lowering from an upright to prizontal position of a drum is limited to 220 pounds 9.79 kgs).		
	friction be surface, a every 30 assumption	the above practices assume a good coefficient of etween the employee's footwear and the walking average male weight and strength, one push, pull lift minutes. Drum handling activities outside these ons require further evaluation with support from afety staff as needed.		
7.	Employees experiencing discomfort resulting from ergonomic-related sources such as computer workstation use, material handling, or other equipment use will report the discomfort to line management and seek a Site occupational medicine provider evaluation.			

## **Ergonomics**

Published Date: 5/17/09

**Effective Date: 5/17/09**Error! Reference source not found.

#	REQUIREMENT	TYPE V or I	SOURCE
8.	The overall effectiveness of controls implemented for ergonomic-related hazards must be periodically assessed using Project/Function developed measures and modified as necessary for continuous improvement.	1	10CFR851.22
9.	Project/Function Safety managers will provide the OS&IH Leadership team feedback on Lessons Learned, Ergonomic-related assessment summaries, results of ergonomic-related injury/illness investigations, etc. to facilitate continuous improvement.	I	10CFR851.26 (b) (1)-(2)

#### 3.0 SOURCES

#### 3.1 Requirements

10 CFR 851, Worker Safety and Health Program 29 CFR 1910, Occupational Safety and Health Standards

#### 3.2 References

PRC-PRO-WKM-079, Job Hazard Analysis

#### 4.0 APPENDIXES

Appendix A – Material Handling Controls

Page 7 of 7

## **Ergonomics**

Published Date: 5/17/09

Effective Date: 5/17/09Error! Reference source not found.

### **Appendix A – Material Handling Controls**

Control Type	Examples
Engineering Controls	Changing the shape of items or handles to allow easier grasp; using counterbalances to stabilize loads; decreasing the distance, height, or weight of objects; providing mechanical devices such as handcarts, hand trucks, fork trucks, cranes, or hoists; reducing the weight manually handled.
Work Practices	Optimizing the load location between knee and shoulder level whenever possible; distributing a load evenly while keeping it close to the body; providing assistance/help; maintaining good physical condition; not exceeding physical or mental abilities; avoiding twisting, pushing, pulling or sliding objects instead of lifting; avoid fatigue from repeated forceful activities.
Administrative Controls	Establishing limits for handling heavy, bulky, or awkward-shaped objects; providing adequate recovery time.
Personal Protective Equipment	Use personal protective equipment to reduce or eliminate ergonomic hazards such as gloves to enhance grip stability on slippery surfaces, hearing protection in high noise areas and clothing appropriate for the prevailing environmental conditions.